

Rustlick™ 606 Rust Preventative

DESCRIPTION

Rustlick™ 606 is a moisture-absorbing rust preventative and corrosion inhibitor designed for long-term in-door use which can be applied to porous, wet surfaces and reduces surface preparation time. It leaves an oily thin-film that is easily removed by wiping, alkaline washing, or vapor degreasing. Rustlick™ 606 is recommended for porous or configured metals.

FEATURES

- Indoor corrosion protection for up to two years
- Spreads into nooks, crannies, pores and gaps
- Leaves a transparent rust-inhibiting film

APPLICATIONS

- For corrosion and rust prevention

DIRECTIONS

Aerosol: Spray on wherever protection is needed, Bulk: Apply by brushing or dipping

HANDLING

Aerosol: Keep away from heat, sparks and open flame. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Bulk: Keep away from heat, sparks and open flame. No smoking. Use only in area provided with appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Wash thoroughly after handling.

STORAGE

Aerosol: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Bulk: Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL

Dispose of contents/container to an approved waste disposal plant.



PROPERTIES

Appearance / Physical State	Aerosol: Aerosol Bulk: Liquid
Odor	Aerosol: Mild Bulk: Characteristic
Melting / Freezing Point	Not Available
Boiling Point / Range	Aerosol: No data available Bulk: 100°C / 212°F
Vapor Pressure	No data available
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	Aerosol:
VOC Content	72%
Color	Red Brown
Flash Point	Aerosol: -104°C / -156°F Bulk: 79°C / 175°F
Density	Not Available
Evaporation Rate	>1
Vapor density	>1
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	Aerosol: 0.86 Bulk: 0.83
Temperature Range	Not Available
4-Ball Weld Load	Not Available

SHELF LIFE INFORMATION

2 years



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



606 Rust Preventative

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
71152	1 gal	case	4	30 lbs
71052	5 gal	pail	1	36 lbs
71552	55 gal	drum	1	411 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved