

APPLICATIONS

- General machining and sawing
- Replacement for "mist" type lubricant and coolant
- Lumber & wood cutting applications
- Moderate-duty
- Vegetable-based, biodegradable lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean before heat treating with soap and water

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

| | |
|-----------------------------|-------------------|
| Appearance / Physical State | Liquid |
| Color | Blue |
| Odor | Mild |
| Boiling Point / Range | >399.2°F (>204°C) |
| Flash Point | 608°F (320°C) |
| Pour Point | -4°F (-20°C) |
| Vapor Pressure | <1 mm Hg |
| Vapor density | >1 |
| Water Solubility | Insoluble. |
| Specific Gravity | 0.92 |
| VOC Content | 0.2 g/l |
| Viscosity | 37 cSt @ 40°C |

AVAILABLE PRODUCTS

| Part No. | Net Contents | Container Type | Units/Case | Approximate Case Weight |
|----------|--------------|----------------|------------|-------------------------|
| LB3000 | 1 gal | bottle | 4 | 34 lbs |
| LB3055 | 55 gal | drum | 1 | 454 lbs |