



Natural Force[®]

Foaming Degreaser

FEATURES

- Non-Corrosive, Citrus-Based Formulation
- Dissolves grease immediately on contact
- Super concentrated formula
- Better alternative than using a corrosive cleaner or harsh solvents
- NSF C1 Registration

APPLICATIONS

- Adhesives
- Adhesive Residue
- Oils
- Carbon
- Inks
- Asphalt
- Grease
- Grime
- Hydraulic Oils
- Markers
- Glues
- Tar

DIRECTIONS

Spray directly onto greasy surface, agitate if necessary, then wipe clean with damp cloth or sponge.

HANDLING

Do not pierce or burn, even after use. Wear protective gloves and eye protection. If in eyes, rinse cautiously with water for several minutes. Get medical attention and access the Safety Data Sheet if necessary, for situations not mentioned.

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. KEEP OUT OF REACH OF CHILDREN.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.



PROPERTIES

Appearance / Physical State	Aerosol
Odor	Citrus
Melting / Freezing Point	N/A
Boiling Point / Range	N/A
Vapor Pressure	110 psig @ 21°C (70°F)
Partition Coefficient	Not determined
Propellant	Propane/Isobutane blend
VOC Content	10.00%
Color	White
Vapor density	> 1 (Air = 1)
Auto-Ignition Temperature	Product is not self-igniting
Density	0.99 g/cm (8.262 lbs/gal) @ 20°C (68°F)
pH Value	10.2 - 11.2
Water Solubility	Soluble

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
36120	17 oz / 482 g	aerosol	12	17 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved