



OVS 210-21

Heavy-Duty Stamping Lubricant

FEATURES

- Provides excellent tool life
- Can dilute wide range
- Can be welded without wash
- Will not build up in dies

APPLICATIONS

- Medium & Heavy-Duty Stamping including:
- Automotive heavier-duty flanges, control arms
- Suspension components
- Seat Frame components
- Many others - please contact us with questions.

DIRECTIONS

Dilute Metal Mates OVS with water to suit the specific application. Slowly add water to lubricant while mixing. Water quality enhances the performance of all water-dilutable lubricants.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

DISPOSAL

Absorb on suitable material and follow procedures shown on SDS. Dispose of in a manner that is recommended by local, state, provincial, and federal laws and regulations.



PROPERTIES

Odor	mild
pH Value	8.3-9.3
Specific Gravity	0.98
Flash Point	>200F (>93C)
Boiling Point / Range	212F (100C)
Vapor Pressure	<1
Vapor Density	Heavier than air
Total Chlorine	Y
Dilution Ratio	Typical Dilution: 3:1 to 6:1 (33-17%)
Prop 65 Warning	Yes
Active sulfur content	None

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM2002	5 gal	pail	1	creamy tan
MM2003	55 gal	drum	1	creamy tan
MM2006	330 gal	tote	1	creamy tan



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved